



Crimp Top Service Tee

BF Series

APPLICATION

Provides a PE service pipe connection to a metallic gas main which has been drilled and tapped with a parallel BSP thread.

DESCRIPTION

Comprising a Tee Body compatible with site tapped parallel threads to BS21 (Rp) specification, the fitting has an internal Stopper Plug to allow it to be installed under pressure. The fitting has a shaped Washer to compress the rubber Gasket to make a gas tight seal between the Body and surface of the main. The outlet uses a Crimp joint to connect to the PE service pipe. Suitable for low and medium pressure gas mains.

CONSTRUCTION

- Body (1) and Plug (11): Malleable Iron or SG Iron
- Washer (6) & Back Nut (7): Malleable Iron or SG Iron
- Gasket (10) & Seals (10): NBR Rubber
- Anti-Shear Bush (5): EPDM Rubber
- Crimp Ring (4): Copper – annealed
- Insulation Washer (2) & Stopper (9): Engineering plastic
- Corrosion protection: Light oil film – must be site protected.

INSTALLATION

Crimp Top Service Tees are supplied suitable for site installation using gas under pressure drilling machines conforming to GIS/E1 specification such as WASK Teeset®. The EMID joint should be installed following the instructions for the alignment and tightening of the Back Nut included with the product. The Crimp joint should be installed using the correct WASK Crimp tool. PE anti-shear sleeves should be fitted before making final connection. The internal Stopper Plug can be operated using the WASK tool BE0034. Fittings must have an approved site corrosion protection system applied after installation and pressure testing.



Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication & reserves the right to change without notice.

SPECIFICATION

Meets GIS/F2:2013 & GIS/PL3:2014 requirements, BSI Kite Mark certified – KM611750 & KM587336.
 Maximum Operating Pressure (MOP) = 2.0 Bar.


METALLIC PIPE SIZES

Available in sizes from 20mm to 32mm with threads 3/4" BSP or 1" BSP, with special parallel BS21:1985 (Rs) thread form for use on gas mains up to 42" nominal diameter.

DIMENSIONS

May also be used on steel mains with thin walls (less than 3 thread pitches = 7mm) or non-metallic gas mains using a suitable WASK Pressure Drilling Saddle, see the AA Series range for details.

SIZE = PE x NOMINAL INLET THREAD DIAMETER		
SIZE PE x BSP (Rs)	MAIN MIN Ø	ANTI-SHEAR SLEEVE Ø
20 SDR9 x 3/4"	3"	50mm
20 SDR9 x 1"	4"	50mm
25 SDR11 x 3/4"	3"	50mm
25 SDR11 x 1"	4"	50mm
32 SDR11 x 3/4"	3"	50mm
32 SDR11 x 1"	4"	50mm



To visit our Video Library go to:
www.youtube.com/user/CraneBSU



46-48 WILBURY WAY, HITCHIN,
 HERTFORDSHIRE, SG4 0UD
 TELEPHONE: +44 (0)1462 443225
 TELEPHONE: +44 (0)1462 443226
 FAX: +44 (0)1462 443311
 EMAIL: sales@wask-uk.com
www.wask-uk.com



FM 00311 EMS 553775

- Designed and manufactured under quality management systems in accordance with BS EN ISO 9001.

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

W_CTST_0121_v1